

09-29-00

A

SIEMENS Corporation

PATENT APPLICATION

Attorney Docket No. : 00 P 7411 US01

IPD-West Coast
186 Wood Avenue South
Iselin, NJ 08830

Express Mail Label No.: EL485650932US

Date of Deposit: September 27, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

THE ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

TRANSMITTAL LETTER FOR NEW APPLICATION

Sir:

Transmitted herewith for filing is a(n) ☒ Original patent application.
☐ Utility ☐ Design ☐ Continuation-in-part application

INVENTOR(S): Klaus Schulz and Schelto Van Doorn

TITLE: PLUGGABLE TRANSCEIVER LATCHING MECHANISM

Enclosed with this transmittal (submitted in duplicate) are the following:

- ☒ 10 page specification.
☒ 3 sheets of drawings ☐ formal drawings ☒ informal drawings (one set)
☒ The Declaration and Power of Attorney ☒ signed ☐ unsigned
☒ An Assignment Transmittal and Assignment to Infineon Technologies North America Corp.
☒ Information Disclosure Statement with PTO1449 and five (5) references.
☒ Filing fee has been calculated as shown below (other than small entity):


For	Number Filed	Number Extra	Rate	Additional Fees
Total Claims	20 - 20	= 0	x \$ 18	\$ 0.00
Indep. Claims	3 - 3	= 0	x \$ 78	\$ 0.00
<input type="checkbox"/> First Presentation of a Multiple Dependent Claim			x \$260	\$ 0.00
			Basic filing Fee	\$690.00
			Total	\$690.00

Please charge my Deposit Account No. 19-2179 in the amount of \$690.00. The Commissioner is hereby authorized to charge any fees that may be required, or credit any overpayment to Deposit Account No. 19-2179 pursuant to 37 CFR 1.25. A duplicate copy of this sheet is enclosed.

PLEASE MAIL CORRESPONDENCE TO:

Siemens Corporation
 Attn: Elsa Keller, Legal Administrator
 Intellectual Property Department
 186 Wood Avenue South
 Iselin, NJ 08830

Respectfully submitted,



Heather S. Vance
 Attorney for Applicant(s)

Reg. No.: 39,033

Date: 9/27/00

Telephone: (408) 492-5085

09/27/00

09/27/00 U.S. PTO

09/27/00 U.S. PTO

09/27/00

09/27/00

09/27/00 U.S. PTO

Atty Docket No.: 00 P 7411 US01

IN THE
UNITED STATES PATENT AND TRADEMARK OFFICE

This is a U.S. Patent Application for:

Title: PLUGGABLE TRANSCEIVER LATCHING MECHANISM

Inventor #1: Klaus Schulz
Address: Im Domstift 39, 12309, Berlin, Germany
Citizenship: Germany

Inventor #2: Schelto Van Doorn
Address: 6569 Fifewood Ct., San Jose, CA 95120
Citizenship: Netherlands

PLUGGABLE TRANSCEIVER LATCHING MECHANISM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/175,610, which was filed January 11, 2000, by Schelto van Doorn and Klaus Schulz, and is entitled "Latch Mechanism."

TECHNICAL FIELD

This invention relates to pluggable transceivers and cages and to systems and methods of latching a pluggable transceiver to a cage.

BACKGROUND

Transmission cables may be used to transmit data between workstations, mainframes and other computers, as well as provide data connections to mass storage devices and other peripheral devices. Data may be transferred using a variety of transmission cable technologies, including multimode optical fiber cables, single mode optical fiber cables, and copper cables (e.g., twinax and coax copper cables). Standard pluggable transceiver modules have been developed to transition between different transfer media and the electronic components inside a computer or peripheral device. A pluggable transceiver module produces a standardized output in accordance with prescribed protocols, regardless of the medium (e.g., optical fiber or copper) through which the data is transmitted or received. A transceiver module typically plugs into a cage that extends out of the rear panel of a computer or peripheral device. The cage connects the transceiver module to a motherboard or circuit card in the computer or peripheral device.

SUMMARY

The invention features novel systems and methods for latching a pluggable transceiver to and unlatching the pluggable transceiver from a cage.

In one aspect of the invention, a pluggable transceiver comprises a housing and a cam. The housing has a front end configured to couple to a transmission cable and a back end configured to be inserted into a cage. The cam is disposed on an exposed outer surface of the transceiver housing and is configured to

displace a cage latch and engage a cage slot upon insertion of the transceiver housing into the cage.

Embodiments in accordance with this aspect of the invention may include one or more of the following features.

5 The cam preferably has a chamfered surface exposed for contact with the cage latch as the transceiver is being inserted into the cage. The chamfered surface of the cam may be rectangular or it may taper from the front end to the back end of the transceiver housing.

10 The pluggable transceiver may include a release mechanism disposed on a surface of the transceiver housing and configured to disengage the cam from the cage slot. The release mechanism may include a release block configured to slide into engagement with the cage latch to disengage the cam from the cage slot. The release block preferably comprises a chamfered surface exposed for contact with the cage latch.

15 In another aspect of the invention, a cage comprises a housing and a latch. The housing has a front end for receiving a pluggable transceiver and defines a slot for engaging a transceiver cam. The latch is disposed at the front end of the cage housing. The latch also is configured to bend outwardly from an original position in response to a force applied by the transceiver cam as the transceiver is
20 being inserted into the cage and to resiliently return to the original position upon engagement of the transceiver cam with the slot defined in the front end of the cage housing.

Embodiments in accordance with this aspect of the invention may include one or more of the following features.

25 The latch preferably includes a front end having an inner surface that flares outwardly away from an interior region of the cage housing. The cage latch may be formed integrally with the cage housing. The cage housing preferably is configured to shield against electromagnetic interference.

30 The cage may include an ejection mechanism configured to engage and apply an ejection force against the pluggable transceiver when disposed within the cage housing. The cage also may include a circuit card connector disposed in a back end of the cage housing and configured to couple the pluggable transceiver

to a circuit card. The cage housing preferably is configured to engage an opening in an electromagnetic enclosure.

In another aspect, the invention features a data coupling system comprising the above-defined pluggable transceiver and cage.

5 Among the advantages of the invention are the following.

The invention provides an elegant and cost-effective way to securely latch a pluggable transceiver to a cage. In addition, by incorporating the latch into the cage, the invention avoids exposure of the latching mechanism to edges and other surfaces on which the latch may catch during normal use conditions. As a result, 10 the invention reduces the likelihood that the latch will become deformed or broken, improving the durability and expected use-life of the latch.

Other features and advantages of the invention will become apparent from the following description, including the drawings and the claims.

DESCRIPTION OF DRAWINGS

15 FIG. 1A is a diagrammatic cross-sectional side view of a transceiver module, a cage that extends out of the rear panel of an electronic equipment enclosure, and a transmission cable.

FIG. 1B is a diagrammatic cross-sectional side view of the transmission cable, transceiver module and cage of FIG. 1A connected together.

20 FIG. 2 is a diagrammatic exploded view of the cage of FIGS. 1A and 1B.

FIG. 3A is a diagrammatic bottom view of the transceiver of FIGS. 1A and 1B.

FIG. 3B is a diagrammatic cross-sectional view of the transceiver of FIGS. 1A and 1B, taken along the line 3B-3B in FIG. 3A.

25 FIG. 4A is a diagrammatic bottom view of an alternative transceiver.

FIG. 4B is a diagrammatic cross-sectional view of the transceiver of FIG. 3A taken along the line 4B-4B.

DETAILED DESCRIPTION

In the following description, like reference numbers are used to identify 30 like elements. Furthermore, the drawings are intended to illustrate major features of exemplary embodiments in a diagrammatic manner. The drawings are not

intended to depict every feature of actual embodiments or relative dimensions of the depicted elements, and are not drawn to scale.

Referring to FIGS. 1A and 1B, in one embodiment, a data coupling system 10 includes a transmission cable 14 and an associated cable connector 16. Cable connector 16 is configured to plug into a mating connector 18 of a pluggable transceiver module 20 that, in turn, is configured to plug into a receptacle assembly 22. Receptacle assembly 22 includes a cage 24 mounted on a circuit card (or motherboard) 26, and a circuit card (or host interface) connector 28 that electrically connects transceiver module 20 to circuit card 26. Cage 24 extends through a mounting panel opening 30 in a rear panel 32 of an electromagnetically shielded electronic equipment enclosure. Transceiver module 20 is configured to transition between circuit card 26 and the transfer medium of transmission cable 14. As shown in FIG. 1B, in operation, transceiver module 20 plugs into cage 24 and cable connector 16 plugs into transceiver module connector 18.

As explained in detail below, cage 24 includes a latch 40 and a slot 42 that engages a mating cam 44 on a bottom surface of transceiver module 20. Latch 40 has a front end with an inner surface 45 that flares outwardly away from the interior of cage 24. As transceiver module 20 is being inserted into cage 24, cam 44 engages the flared inner surface 45 of latch 40 and displaces the front end of latch 40 outwardly. As soon as the rear end of cam 44 clears the rear edge of slot 42, cam 44 slides into slot 42 and the front end of latch 40 resiliently returns to its original position to hold transceiver module in place. Incorporating latch 40 into cage 24 avoids exposure of the latching mechanism to edges and other surfaces on which the latch may catch during normal use conditions. This feature reduces the likelihood that the latch will become deformed or broken, thereby improving the durability and expected use-life of the latch. Cage 24 also includes an ejection mechanism 46 that is configured to apply an ejection force against the back end of transceiver module 20 when transceiver module 20 is plugged into cage 24.

Transceiver module 20 may be released from cage 24 by displacing the front end of latch 40 until the rear edge of cam 44 clears the rear edge of slot 42. In some embodiments, the front end of latch 40 may be displaced using a tool, such as a screwdriver. Other transceiver module embodiments may include a release mechanism 48 formed from a release block 50, which is slidable toward

and away from the back end of transceiver module 20 within a longitudinal slot defined in the bottom surface of transceiver module 20. In operation, a user may press release block 50 toward cage 24 until latch 40 has been displaced outwardly by an amount sufficient for the rear edge of cam 44 to clear the rear edge of slot 42, at which point the ejection force applied by ejection mechanism 46 forces transceiver module 20 out of cage 24.

Referring to FIG. 2, in one embodiment, cage 24 is constructed out of metallic sheets that are folded and stamped to form a top half 60 and a bottom half 62. Bottom half 62 of cage 24 includes a series of lugs 64 that latch onto a respective series of corresponding slots 66 defined in top half 60 of cage 24. Ejection mechanism 46 is formed integrally with bottom half 60 by bending the walls at the back end of the bottom half 62 of cage 24 toward the front end of cage 24. Top half 60 of cage 24 also includes a series of integral resilient springs 68 that are configured to engage an opening in a rear panel of an electromagnetically shielded electronic equipment enclosure. Cage 24 preferably is formed from material sheets that are designed to shield against electromagnetic interference, such as stainless steel or other conductive material.

Referring to FIGS. 3A and 3B, in one transceiver module embodiment, cam 44 includes a chamfered surface 70 that tapers from the front end to the back end of transceiver module 20. Tapering chamfered surface 70 reduces the area of contact between cam 44 and latch 40 and, thereby reduces the force needed to insert transceiver module 40 into cage 24. Release block 50 also has a chamfered surface 72 for engaging the flared front end 45 of latch 40. As shown in FIGS. 4A and 4B, in other embodiments, the chamfered surface of cam 44 may have a non-tapered shape. For example, in one embodiment, cam 44 may include a rectangular chamfered surface 74. In each embodiment, the shape of cage slot 42 is selected to match the profile of cam 44. Thus, latch 40 would have a triangular slot for engaging the transceiver module embodiment of FIGS. 3A and 3B, and latch 40 would have a rectangular slot for engaging the transceiver module embodiment of FIGS. 4A and 4B. The physical dimensions of cam 44 are selected based at least in part upon the material composition of cam 44 and the desired retention force between cam 44 and latch 40 when transceiver module 20 is latched inside cage 24 (e.g., approximately 60-100 Newtons).

Data coupling system 10 may incorporate a variety of different transfer media and media connectors. For example, transmission cable 14 may be an optical fiber cable (e.g., a single mode or a multimode optical fiber cable) or an electrical (copper) cable (e.g., a twinax or a coax copper cable). Cable connector 5 16 and transceiver connector 18 may conform to any one of a variety of optical and copper interface standards, including HSSDC2-type, RJ-type, SC-type, SG-type, ST-type and LC-type connectors, ribbon cable connectors, and twinax and coaxial cable connectors (e.g., SMA connectors). Cage 28 also may conform to a variety of host interface standards, including the MIA (Media Interface Adapter) 10 standard and the recently proposed MSA standard.

Other embodiments are within the scope of the claims.

WHAT IS CLAIMED IS:

1 1. A pluggable transceiver, comprising:
2 a housing having a front end configured to couple to a transmission cable
3 and a back end configured to be inserted into a cage; and
4 a cam disposed on an exposed outer surface of the transceiver housing and
5 configured to displace a cage latch and engage a cage slot upon insertion of the
6 transceiver housing into the cage.

1 2. The pluggable transceiver of claim 1, wherein the cam has a
2 chamfered surface exposed for contact with the cage latch as the transceiver is
3 being inserted into the cage.

1 3. The pluggable transceiver of claim 2, wherein the chamfered surface
2 of the cam is rectangular.

1 4. The pluggable transceiver of claim 2, wherein the chamfered surface
2 of the cam tapers from the front end to the back end of the transceiver housing.

1 5. The pluggable transceiver of claim 1, further comprising a release
2 mechanism disposed on a surface of the transceiver housing and configured to
3 disengage the cam from the cage slot.

1 6. The pluggable transceiver of claim 5, wherein the release
2 mechanism comprises a release block configured to slide into engagement with
3 the cage latch to disengage the cam from the cage slot.

1 7. The pluggable transceiver of claim 6, wherein the release block
2 comprises a chamfered surface exposed for contact with the cage latch.

1 8. A cage, comprising:
2 a housing having a front end for receiving a pluggable transceiver and
3 defining a slot for engaging a transceiver cam; and
4 a latch disposed at the front end of the cage housing and configured to
5 bend outwardly from an original position in response to a force applied by the
6 transceiver cam as the transceiver is being inserted into the cage and to resiliently

7 return to the original position upon engagement of the transceiver cam with the
8 slot defined in the front end of the cage housing.

1 9. The cage of claim 8, wherein the latch includes a front end having
2 an inner surface that flares outwardly away from an interior region of the cage
3 housing.

1 10. The cage of claim 8, wherein the cage housing is configured to
2 shield against electromagnetic interference.

1 11. The cage of claim 8, further comprising an ejection mechanism
2 configured to engage and apply an ejection force against the pluggable transceiver
3 when disposed within the cage housing.

1 12. The cage of claim 8, further comprising a circuit card connector
2 disposed in a back end of the cage housing and configured to couple the
3 pluggable transceiver to a circuit card.

1 13. The cage of claim 8, wherein the cage latch is formed integrally with
2 the cage housing.

1 14. The cage of claim 8, wherein the cage housing is configured to
2 engage an opening in an electromagnetic enclosure.

1 15. A data coupling system, comprising:
2 a pluggable transceiver comprising a housing having a front end configured
3 to couple to a transmission cable, and a cam disposed on an exposed outer
4 surface of the transceiver housing; and
5 a cage comprising a housing having a front end for receiving the pluggable
6 transceiver and defining a slot for engaging the transceiver cam, and a latch
7 disposed at the front end of the cage housing;
8 wherein the transceiver cam is configured to displace the cage latch and
9 engage the cage slot upon insertion of the transceiver housing into the cage, and
10 the cage latch is configured to bend outwardly from an original position in
11 response to a force applied by the transceiver cam as the transceiver is being
12 inserted into the cage and to resiliently return to the original position upon

13 engagement of the transceiver cam with the slot defined in the front end of the
14 cage housing.

1 16. The data coupling system of claim 15, wherein the cam has a
2 chamfered surface exposed for contact with the cage latch as the transceiver is
3 being inserted into the cage.

1 17. The data coupling system of claim 15, further comprising a release
2 mechanism disposed on a surface of the transceiver housing and configured to
3 disengage the cam from the cage slot.

1 18. The data coupling system of claim 17, wherein the release
2 mechanism comprises a release block configured to slide into engagement with
3 the cage latch to disengage the cam from the cage slot.

1 19. The data coupling system of claim 18, wherein the release block
2 comprises a chamfered surface exposed for contact with the cage latch.

1 20. The data coupling system of claim 15, wherein the cage further
2 comprises an ejection mechanism configured to engage and apply an ejection
3 force against the pluggable transceiver when disposed within the cage housing.

PLUGGABLE TRANSCEIVER LATCHING MECHANISM

ABSTRACT

The invention features novel systems and methods for latching a pluggable transceiver to and unlatching the pluggable transceiver from a cage. In one aspect, a pluggable transceiver includes a housing and a cam. The housing has a front end configured to couple to a transmission cable and a back end configured to be inserted into a cage. The cam is disposed on an exposed outer surface of the transceiver housing and is configured to displace a cage latch and engage a cage slot upon insertion of the transceiver housing into the cage. In another aspect, a cage includes a housing and a latch. The housing has a front end for receiving a pluggable transceiver and defines a slot for engaging a transceiver cam. The latch is disposed at the front end of the cage housing. The latch also is configured to bend outwardly from an original position in response to a force applied by the transceiver cam as the transceiver is being inserted into the cage and to resiliently return to the original position upon engagement of the transceiver cam with the slot defined in the front end of the cage housing. A data coupling system comprising the above-defined pluggable transceiver and cage also is described.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B

DECLARATION FOR PATENT APPLICATION & POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

PLUGGABLE TRANSCEIVER LATCHING MECHANISM

the specification of which (check one)

☒ is attached hereto.

☐ was filed on _____ as Application Serial No.

and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Codes, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

Priority claimed

(Number)	(Country)	(Day/month/year filed)	Yes	No

(Number)	(Country)	(Day/month/year filed)	Yes	No

(Number)	(Country)	(Day/month/year filed)	Yes	No

I hereby claim the benefits under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose

material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing date)	(Status) (patented,pending,abandoned)
--------------------------	---------------	--

(Application Serial No.)	(Filing date)	(Status) (patented,pending,abandoned)
--------------------------	---------------	--

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application listed below:

60/175,610	January 11, 2000	Pending
------------	------------------	---------

(Application Serial No.)	(Filing date)	(Status)
--------------------------	---------------	----------

Power of Attorney: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Adel A. Ahmed, Reg. No. 29,606; Stanton C. Braden, Reg. No. 32,556; Robert T. Canavan, Reg. No. 37,592; Dexter K. Chin, Reg. No. 38,842; Joseph S. Codispoti, Reg. No. 31,819; Lawrence C. Edelman, Reg. No. 29,299; Mark H. Jay, Reg. No. 27,507; Stuart P. Kaler, Reg. No. 35,913; Rosa S. Kim, Reg. No. 39,728; David W. Laub, Reg. No. 38,708; Peter A. Luccarelli, Jr., Reg. No. 29,750; Jeffrey P. Morris, Reg. No. 25,307; Pasquale Musacchio, Reg. No. 36,876; Donald B. Paschburg, Reg. No. 33,753; Erik C. Swanson, Reg. No. 40,194; Heather S. Vance, Reg. No. 39,033; Scott T. Weingaertner, Reg. No. 37,756; Robert A. Whitman, Reg. No. 36,966; and Ira Lee Zebrak, Reg. No. 31,147.

Send correspondence to:

Direct telephone calls to:

Siemens Corporation
Intellectual Property Department
186 Wood Avenue South
Iselin, N.J. 08830

Elsa Keller
Legal Administrator (732) 321-3026

I hereby declare that all statements made herein on my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the State Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of first
joint inventor:

Klaus Schulz

Inventor's signature:

Klaus Schulz

Date:

2000-09-19

Residence:

Berlin, Germany

Citizenship:

Germany


Post Office Address:

Im Domstift 39, 12309, Berlin, Germany

Full name of second
joint inventor:

Schelto Van Doorn

Inventor's signature:



Date:

2000/9/21

Residence:

San Jose, CA

Citizenship:

Netherlands

Post Office Address:

6569 Fifewood Ct., San Jose, CA 9512